

Architectural Whites Floor Tiles

glazed floor tiles

Product description Glazed, porcelain floor tiles, manufactured in accordance with EN 14411 Bib and ASTM standards.

Sizes 6" x 6"

Usage area Our floor tiles may be used in residential and light commercial environments.
Our glazed floor tiles are not frost proof and cannot be used exterior.

Technical data / conformity standards

Technical data	ASTM test	Requirements	Royal Mosa
Water absorption	C 373	≤ 0.5%	≤ 0.3%
Breaking strength	C 648	≥ 250 lbs	-
Bond strength	C 482	≥ 50 psi	246 psi
Actual thickness	C 499		0.24 inch = 8/32"
Coefficient of friction	C 1028	≥ 0.6	0.85 (dry) / 0.58 (wet)
PEI*		I - V	483V, 484V: Class IV 485V: Class III

* ISO 10545-7

Our limited warranty Royal Mosa warrants that its first choice ceramic tiles are manufactured to ANSI-Standards A137.1 and meet or exceed the requirements of the standard.
Please consult the company's Terms and Conditions for Sale for complete product warranty details.

Maintenance Please consult our Cleaning and Maintenance leaflet.

Like any material, Royal Mosa's ceramic tiles can become slippery when wet. Care should be taken to keep the surface dry at all times. Our tiles should be installed in accordance with the current application guides of the Tile Council of America and/or American National Standards Institute guides and standards. Errors and omissions excepted.

This technical product sheet replaces all previous versions. For the most actual version see www.mosa.nl.



Royal Mosa
Meerssenerweg 358
P.O. Box 1026
NL-6201 BA Maastricht
T +31 (0)43 368 92 29
F +31 (0)43 368 93 56
usa@mosa.nl
www.mosa.nl

