

Wall Tile Collections

glazed wall tiles

10thirty®, 15thirty Collection, Architectural Whites, Global Collection, Kho Liang le Collection®, Linea LED, More than white, Mosa Colors®, Mosa Matt Collection®, The White Collection

Product description Glazed, dry pressed ceramic wall tiles, manufactured in accordance with EN 14411 BIII and ASTM standards. Mosa wall tiles are modular, including a 1/8" joint. At least one fully glazed edge is available. See below for details.

Sizes	One glazed edge	Series
4" x 4"	Yes	Kho Liang le Collection® Mosa Colors®
4" x 8"	Yes, 8" edge	Global Collection
4" x 12"	Yes, 4" edge; 12" edge special request	10thirty®, Mosa Matt Collection®
6" x 6"	Yes	Architectural Whites, Global Collection, Mosa Colors®, Mosa Matt Collection®
6" x 8"	Yes, 6" or 8" edge available	Architectural Whites
6" x 12"	Yes, 6" edge; 12" edge special request	15thirty Collection, Mosa Colors®, Mosa Matt Collection®
6" x 18"	No	Linea LED
8" x 8"	Yes	Architectural Whites
8" x 10"	Yes, 10" edge	Architectural Whites
12" x 18"	Yes, 18" edge	Linea LED, The White Collection
12" x 24"	No	More than white

Usage area Our wall tiles may be used in residential and commercial environments. Our wall tiles are not frost proof and cannot be used exterior (except 10thirty frost proof 13210 and 13310).

Technical data / conformity standards	Technical data	ASTM test	Requirements	Royal Mosa
	Water absorption	C 373	≤ 20%	16.74%
	Bond strength	C 482	≥ 50 psi	79 psi
	Facial dimension (sides)	C 499	≤ 4%	2.65 ≤ x ≤ 2.92%
	Facial dimension (range)	C 499	≤ 0.6%	0.27%
	Range of thickness	C 499	≤ 0.031 inch	0.009 ≤ x ≤ 0.010 inch
	Actual thickness	C 499		0.21 - 0.43 inch = 7/32" / 14/32" *
	Warp (edge)	C 485	-0.3 ≤ x ≤ 0.4%	max. -0.11%
	Warp (diagonal)	C 485	≤ 0.5%	max. -0.04%
	Wedging	C 502	≤ 0.6%	max. -0.21%
	Crazing	C 424	150 psi	pass
	Thermal shock	C 484	no evidence	pass

Data from 6" x 6" to 8" x 10".
* Actual thickness depends on size and series.

Our limited warranty Royal Mosa warrants that its first choice ceramic tiles are manufactured to ANSI-Standards A 137.1 and meet or exceed the requirements of the standard. Please consult the company's Terms and Conditions for Sale for complete product warranty details.

Recycled content Royal Mosa wall tiles are produced with an environmental friendly recycled content of minimum 16%, except the sizes 6" x 6" and 6" x 8", which have a recycled content of minimum 25%. Colors do not contain lead particles hazardous to health or environment.

Maintenance Please consult our Cleaning and Maintenance leaflet.



Our wall tiles should not be installed on high shrinkage water beds. Our tiles should be installed in accordance with the current application guides of the Tile Council of America and/or American National Standards Institute guides and standards. Errors and omissions excepted. This technical product sheet replaces all previous versions. For the most actual version see www.mosa.nl.



Royal Mosa
Meerssenerweg 358
P.O. Box 1026
NL-6201 BA Maastricht
T +31 (0)43 368 92 29
F +31 (0)43 368 93 56
usa@mosa.nl
www.mosa.nl



Mosa Tiles have been certified Silver by MBDC/EPEA, for their material content, recyclability and manufacturing characteristics.