

# Mosa XXS

## unglazed porcelain tiles

**Product description** Unglazed, rectified, porcelain floor tiles, manufactured in accordance with EN 14411 Bla and ASTM standards. Mosa XXS is modular with Romain / Terra and Beige & Brown.

**Sizes** 12" x 12": between 1/16" and 3/32" (= approx. 2 mm) (joint recommendation)

**Usage area** Our frost proof floor tiles may be used in residential and commercial environments.

### Technical data / conformity standards

Technical data	ASTM test	Requirements	Royal Mosa
Water absorption	C 373	≤ 0.5%	surface: < 0.05% body: ≤ 0.3%
Abrasive wear	C 1243	< 175 mm <sup>3</sup>	88 mm <sup>3</sup>
Breaking strength	C 648	≥ 250 lbs	≥ 766 lbs
Bond strength	C 482	≥ 50 psi	246 psi
Facial dimension (range)	C 499	± 0.5%	0.19%
Range of thickness	C 499	≤ 0.04 inch	0.016 < x < 0.019 inch
Actual thickness	C 499		0.40 inch = 13/32"
Warpage (rectified) edge	C 485	± 0.4%	-0.12% ≤ x ≤ 0.02%
Warpage (rectified) diagonal	C 485	± 0.4%	-0.14% ≤ x ≤ -0.02%
Wedging (rectified)	C 502	± 0.25%	-0.14% ≤ x ≤ 0.16%
Freeze-thaw cycle	C 1026		frost proof
Mohs scale	C 1026		8
Modules of rupture	C 674	quartzite 2,000 psi	7,650 psi
Coefficient of friction	C 1028	≥ 0.6	0.81 (dry) / 0.62 (wet)

**Our limited warranty** Royal Mosa warrants that its first choice ceramic tiles are manufactured to ANSI-Standards A 137.1 and meet or exceed the requirements of the standard. Please consult the company's Terms and Conditions for Sale for complete product warranty details.

**Recycled content** Royal Mosa floor tiles are produced with an environmental friendly recycled content of minimum 20%. Colors do not contain lead particles hazardous to health or environment.

**Maintenance** Please consult our Cleaning and Maintenance leaflet.

Like any material, Royal Mosa's ceramic tiles can become slippery when wet. Care should be taken to keep the surface dry at all times. Our tiles should be installed in accordance with the current application guides of the Tile Council of America and/or American National Standards Institute guides and standards. Errors and omissions excepted.

This technical product sheet replaces all previous versions. For the most actual version see [www.mosa.nl](http://www.mosa.nl).



**Royal Mosa**  
Meerssenerweg 358  
P.O. Box 1026  
NL-6201 BA Maastricht  
T +31 (0)43 368 92 29  
F +31 (0)43 368 93 56  
[usa@mosa.nl](mailto:usa@mosa.nl)  
[www.mosa.nl](http://www.mosa.nl)